

19-02-2001

PCT/SE00/039

GLMSPAM

ART 34 AMDT

WO 00/42450

PCT/SE00/00089

13

CLAIMS

1. A method of detecting an article identification tag (30) having at least one electrically conductive member (31-3n), wherein, for each of said at least one member (31-3n), an alternating electric current is caused to flow through said member, a frequency of the alternating electric current is varied, and a corresponding variation in impedance of said member is monitored, characterized by the steps of

detecting a discontinuity in said variation in impedance; and

detecting the frequency of the alternating electric current, at which frequency said discontinuity appears.

15

2. A method according to claim 1, wherein each of said at least one electrically conductive member (31-3n) has one of a predetermined diameter, a predetermined electrical resistivity or a predetermined magnetic permeability, and wherein said predetermined diameter, resistivity or permeability is mapped to information about an identity of the tag (30).

3. A method as in claim 1 or 2, wherein the alternating electric current is induced in said at least one electrically conductive member (31-3n) by exposing the tag (30) to an alternating electromagnetic field.

4. A method as in any preceding claim, wherein the alternating electric current is induced in said at least one electrically conductive member (31-3n) by exposing the tag (30) to a magnetic field.

15-02-2001

PCT/SE00/00089

GEMSPAM

WO 00/42450

PCT/SE00/00089

14

5. A method as in any preceding claim, wherein said at least one electrically conductive member (31-3n) is an elongated metallic member having the form of a wire, strip or ribbon.

5

6. A method as in claim 5, wherein the elongated magnetic member (31-3n) comprises a non-magnetic metal, preferably copper or aluminium.

10

7. A method as in claim 5, wherein the elongated metallic member comprises a magnetic material, preferably iron, steel or an amorphous metal alloy.

8. An article identification tag (30) comprising a plurality of electrically conductive members (31-3n), characterized in that each of the electrically conductive members (31-3n) has a unique predetermined diameter.

9. A tag as in claim 8, wherein the electrically conductive members (31-3n) are formed as metallic wires, strips or ribbons.

10. A tag as in claim 9, wherein the metallic wires, strips or ribbons (31-3n) comprise a non-magnetic metal, preferably copper or aluminium.

11. A tag as in claim 9, wherein the metallic wires, strips or ribbons comprise a magnetic material, preferably iron, steel or an amorphous metal alloy.

30

13-02-2001

PCT/SE00/000009

CLMSPAM

WO 00/42450

PCT/SE00/000009

15

12. A tag as in any of claims 8 to 11, wherein at least some of the electrically conductive members (35, 36) have galvanic contact with each other.

- 5 13. A tag as in any of claims 8 to 12, wherein the electrically conductive members (34) are formed by an elongated element having sections of different diameters.